

# POS790 Series

15"/17" Metal POS Terminal / Panel PC

**POS 790** Series is a revolution All-in-One Metal Touch Screen POS Terminal or Digital Signage or Panel PC for the harsh retail or hospitality environment. Its ultra slim front bezel, water and grease resistant, exquisite stainless steel enclosure and rugged construction indeed are the best solution of any harsh environment. POS790 series is another powerful offering in restaurant, information kiosk, industrial automation, digital signage, commercial ads and healthcare. The sealed rugged housing is made by stainless steel and water & grease resistant for the harshest environment.



Metal Black POS Terminal



Stainless Steel POS Terminal

## Features



1. Rugged metal housing and NEMA 4 / IP 65 dust & water proof display front.



4. Sealed rear cover and fanless/no air-vent design for the harshest environment  
*(for POS79xFL fanless models only)*



2. 15", 17" display is 4:3



5. Slim HDD bay design for easy service and built-in speakers, and cable cover (option)  
*(for POS79x performance models only)*



3. Rich I/O ports provides excellent peripheral connectivity



6. Ultra slim 30mm thickness stepping design; optional die-casting desktop stand

## POS 790 Series

A powerful offering in digital signage, commercial ads, information kiosk, retail, hospitality, industrial automation and healthcare

### Specification

Model Name	POS790	
Motherboard	B68	B98
Processor	Intel® Atom™ N270 Processor 1.6GHz L2 512K FSB 533MHz	Intel® Celeron® M 1.86G / Core™ 2 Duo 1.66G / Core™ Duo 2.0G
Chipset	Intel® 945GSE Express + ICH7M	Intel® 945GME + ICH 7M FSB 533 / 667MHz
System Memory	2 x DDR2 DIMM up to 2GB	2 x DDR2 DIMM socket up to 4GB FSB 533 / 667MHz
Graphic Memory	Share system memory up to 224MB	Share system memory up to 244MB
<b>LCD Touch Panel</b>		
LCD Size	POS795: 15" TFT LCD POS797: 17" TFT LCD	
Brightness	POS795: 250 cd/m <sup>2</sup> POS797: 300 cd/m <sup>2</sup>	
Resolution	POS795: 1024x768 POS797: 1280x1024	
Touch Screen	Resistive	
Tilt Adjustment	0° ~ 90°	
<b>Storage Device</b>		
Hard Drive	1 x 2.5" SATA HDD bay	
Flash Memory	Compact Flash Memory (Type I & II) or SSD (option)	
<b>Expansion</b>		
Mini PCI-E Slot	1 x support 802.11 b/g/n WLAN card	N/A
Mini PCI Slot	N/A	1 x support 802.11 a/b/g WLAN card
<b>Expansion I/O Ports</b>		
USB Port	4 x USB 2.0 Type A	
PS/2	1	
Serial Port	4 x RJ 45 COM (COM 3 / COM 4 with 5V/12V by jumper )	
Parallel Port	1 x D-sub 25F	
LAN Port	1 x RJ-45 (10/100/1000Mbps Giga LAN)	
DC Jack	1 x Latch Type	
Cash Drawer Port	Support cash drawer 1 x (12V / 24V)	
Audio Jack	1 x Mic-in, 1 x Line-out	
Power switch	1	
<b>Audio</b>		
Speaker	N/A (Ventless)	2 x Speakers
<b>Power</b>		
	Power Adapter (DC 90W, 19V, 4.7A)	
<b>Peripheral</b>		
MSR	MSR (PS/2)	
Customer Display	VFD display 2 x 20 characters (COM)	
Cable Cover	Metal Cable cover with pen screws	
<b>Communication</b>		
Wireless LAN	802.11 b/g or n wireless LAN card & Antenna (option)	
<b>Certificate</b>		
EMC & Safety	FCC Class A / CE Mark / LVD	
<b>Environment</b>		
Operating Temperature	0°C ~ 40°C (32°F ~ 104°F)	
Storage Temperature	-20° ~ 60°C (-4°F ~ 140°F)	
Operating Humidity	5% - 95% RH non-condensing	
Storage Humidity	5% - 95% RH non-condensing	
Dust & Water Proof	NEMA 4 / IP65 (front)	
Dimension (W x D x H)	POS795 LCD 90° tilt angle: 386 x 250 x 370 mm (15.2" x 9.8" x 14.6"), POS795 Wall mount: 386 x 60 x 308 mm (15.2" x 2.4" x 12.1") POS797 LCD 90° tilt angle: 411 x 250 x 390 mm (16.2" x 9.8" x 15.4"), POS797 Wall mount: 411 x 60 x 345 mm (16.2" x 2.4" x 13.6")	
Weight	POS795 (With metal stand): 9.5kg (20.9lbs) POS797 (With metal stand): 10.5kg (23.2lbs)	
Mounting	100mm x 100mm Standard VESA mounting holes	
OS Supported	Windows® XP Pro, POS Ready 2009, Windows® XP Embedded, Windows® CE, Linux, Windows® 7	Windows® XP Pro, POS Ready 2009, Windows® XP Embedded, XP professional for Embedded, Linux, Vista, Windows® 7

Product specifications subject to change without prior notice.

©2010 Flytech Technology Co., Ltd. Registered trademarks and trademarks are property of their respective owners. The specification is subject to change without prior notice. Flytech endeavors to ensure that the information in this document is correct and fairly stated but does not accept liability for any error or omissions. The development of Flytech products and services is continuous, and published information may not be up to date. It is important to check the current position with Flytech.



**FLYTECH Technology Co., Ltd.**  
No.168, Sing-ai Rd.,  
Neihu District, Taipei City 114,  
Taiwan  
Tel: 886-2-8791-4988  
Fax: 886-2-8791-4966  
E-mail: sales@flytech.com.tw  
www.flytech.com

**U.S.A. - California**  
47825 Warm Springs Boulevard, Fremont, CA 94539, USA Tel: 1-510-257-5180 Fax: 1-510-257-5181 E-mail: sales@flytech.com  
**China - Shanghai**  
3F Building 39, No.333 Qin Jiang Rd., Shanghai 200233, P.R.China  
Tel: 86-21-5426-1555 Fax: 86-21-5426-1001 http://www.flytech.com.cn E-mail: sales@flytech.com.cn  
**China - Hong Kong**  
Room 01, 6/F, Block A, Tonic Industrial Centre, 26 Kai Cheung Rd., Kowloon Bay, Kowloon, Hong Kong  
Tel: 852-3525-5800 Fax: 852-2751-7447 http://www.flytech.com.hk E-mail: sales@flytech.com.hk  
**Japan - Nagano Ken**  
2-48-14 Inada, Nagano-Shi, Nagano-Ken, Japan Post Zip Code: 381-0042 Tel: 81-26-259-4804 E-mail: flytech@flytech.co.jp

1004 - P790A