

### Overview

#### At A Glance

- The HP Retail Integrated peripheral options compatible with the HP RP9 Retail System can be purchased and installed separately:
  - HP Retail Integrated Encryption Capable MSR
  - HP Retail Integrated Fingerprint Reader
  - HP Retail Integrated Webcam
  - HP Retail Integrated Barcode Scanner, side mount and bottom mount options
  - Customer-facing 2 line LED Display (2x20); supports complex and non-complex characters
  - Customer-facing 7" Diagonal Non-Touch LCD Display
- HP 3-year Limited Warranty

### Retail Integrated Peripherals

#### HP RP9 Integrated 7-inch Non-Touch Customer Facing Display



#### Top mount and Bottom Mount Options

<b>Models</b>	HP RP9 Integrated 7" NT CFD Btm w/Arm	N3R59AA / M7E27AV
	HP RP9 Integrated 7" NT CFD Top w/Arm	P5A56AA / M7E28AV
<b>Display type</b>	LCD, LED Backlit	
<b>Brightness</b>	250 cd/m2	
<b>Dimensions</b>	183.8*121.6mm	
	7 Inch	
<b>Temperature Range</b>	<b>Operating:</b>	32° to 104° F (0 to 40° C) at 20% to 85% humidity (non-condensing at ambient)
	<b>Non-operating:</b>	32° to 122° F (0° to 50° C) at 5% to 90% humidity (non-condensing at ambient)
<b>Adjustability</b>	Tilt range of motion: 295 degrees	
<b>Weight</b>	Top mount at 560g, long arm at 639g	
<b>Interface</b>	USB	
<b>Power</b>	<b>Operating voltage</b>	+5VDC, 496mA
	<b>Idle current</b>	+5VDC, 128mA
<b>Compatibility</b>	<b>Product</b>	RP9 G1 Retail System
<b>Operating systems</b>	Windows 10 IoT Enterprise for Retail 64-bit*	
	Windows 10 Professional 64-bit*	
	Windows Embedded 8.1 Industry Pro Retail 64-bit**	
	Windows Embedded 8.1 Industry Pro Retail 32-bit**	
	Windows 8.1 Professional 64-bit**	
	Windows 7 Professional 64-bit**	
	Windows 7 Professional 32-bit**	
	Windows Embedded POSReady 7 64-bit**	
	Windows Embedded POSReady 7 32-bit**	

\* Not all features are available in all editions or versions of Windows. Systems may require upgraded and/or separately purchased hardware, drivers, software or BIOS update to take full advantage of Windows functionality. Windows 10 is automatically updated, which is always enabled. ISP fees may apply and additional requirements may apply over time for updates. See <http://www.microsoft.com>

### Retail Integrated Peripherals

\*\* Not all features are available in all editions of Windows. This system may require upgraded and/or separately purchased hardware to take full advantage of Windows functionality. See <http://www.microsoft.com>.

### HP RP9 Retail Ergonomic Stand



<b>Model</b>	HP RP9 Retail Ergonomic Stand	P0Q87AA / M7J40AV
<b>Weight</b>	3.62 kg/ 8 lbs	
	<b>Note:</b> Weight includes power supply	
<b>Features</b>	Industry-standard 100mm VESA pattern Concealed power supply Dual-hinge mechanism Built-in cable-management Bolt-down capabilities allow the terminal to be secured to the counter Quick Release mechanism for tool-less removal	

### Retail Integrated Peripherals

#### HP RP9 Retail Compact Stand



<b>Model</b>	P6D70AV
<b>Weight</b>	2.6 kg / 5.7 lbs <b>Note:</b> Weight includes power supply
<b>Features</b>	Industry-standard 100mm VESA pattern External power supply Single-hinge mechanism Built-in cable-management Bolt-down capabilities allow the terminal to be secured to the counter Quick Release mechanism for tool-less removal

---

### Retail Integrated Peripherals

#### HP RP9 Integrated Side Barcode Scanner



<b>Models:</b>	<b>HP RP9 Integrated Side Barcode Scanner</b>	N3R61AA, M7E29AV Left / M7E30AV Right * <a href="#">March 2016 availability</a>
<b>General</b>	<b>Indicators</b>	Audible and visual read indicators
	<b>Scan direction</b>	Omni-directional
<b>Symbologies</b>	<b>1D / Linear Codes</b>	Autodiscriminates all standard 1D codes including GS1 DataBar™ linear codes.
	<b>2D Codes</b>	Aztec Code; China Han Xin Code; Data Matrix; MaxiCode; Micro QR Code; QR Code
	<b>Postal codes</b>	Australian Post; British Post; China Post; IMB; Japanese Post; KIX Post; Korea Post; Planet Code; Postnet; Royal Mail Code (RM4SCC)
	<b>Stacked codes</b>	EAN/JAN Composites; GS1 DataBar Composites; GS1 DataBar Expanded Stacked; GS1 DataBar Stacked GS1 DataBar Stacked Omnidirect
<b>Depth of field</b> (Typical)	<b>Code 39: 5 mils</b>	6.5 to 21.0 cm
	<b>Code 39: 20 mils</b>	Up to 50.0 cm
	<b>Data Matrix: 15 mils</b>	4.0 to 25.0 cm
	<b>EAN: 13 mils</b>	5.5 to 39.0 cm
<b>Mechanical</b>	<b>Dimensions (LxWxH)</b>	99.3x51.2x59.8 mm
	<b>Weight</b>	138g
	<b>Adjustability</b>	3° to 90° (Tilt range) -180° to +180° (Swivel range)
	<b>Color</b>	HP Black
<b>Interface/Connection</b>	<b>Interface</b>	USB 2.0
	<b>Connection</b>	Type A
<b>Power</b>	<b>Voltage (typical)</b>	5.0V +/- 5% supplied by USB
	<b>Current consumption (typical)</b>	150mA

### Retail Integrated Peripherals

**Drivers**

Windows Native, OPOS, JPOS

**Operating Systems Compatibility**

Windows 10 IoT Enterprise for Retail 64-bit\*, \*\*

Windows 10 Professional 64-bit\*, \*\*\*

Windows Embedded 8.1 Industry Pro Retail 64-bit\*\*

Windows 8.1 Professional 64-bit\*\*

Windows Embedded POSReady 7 64-bit\*\*

Windows Embedded POSReady 7 32-bit\*\*

Windows 7 Professional 64-bit\*\*

Windows 7 Professional 32-bit\*\*

\* Not all features are available in all editions or versions of Windows. Systems may require upgraded and/or separately purchased hardware, drivers, software or BIOS update to take full advantage of Windows functionality. Windows 10 is automatically updated, which is always enabled. ISP fees may apply and additional requirements may apply over time for updates. See <http://www.microsoft.com>

\*\* Not all features are available in all editions of Windows. This system may require upgraded and/or separately purchased hardware to take full advantage of Windows functionality. See <http://www.microsoft.com>.

\*\*\* Full support on all x86-based Windows, NO current support drivers for ARM processor platforms.

---

### Retail Integrated Peripherals

#### HP RP9 Integrated Barcode Scanner - Bottom



<b>Models:</b>	<b>HP RP9 Integrated Barcode Scanner - Bottom</b>	N3R60AA / M7E32AV (Bottom) <i>* March 2016 availability</i>
<b>General</b>	<b>Indicators</b>	Audible and visual read indicators
<b>Symbologies</b>	<b>Scan direction</b>	Omni-directional
	<b>1D / Linear Codes</b>	Autodiscriminates all standard 1D codes including GS1 DataBar™ linear codes.
	<b>2D Codes</b>	Aztec Code; China Han Xin Code; Data Matrix MaxiCode; Micro QR Code; QR Code
	<b>Postal codes</b>	Australian Post; British Post; China Post; IMB; Japanese Post; KIX Post; Korea Post; Planet Code; Postnet; Royal Mail Code (RM4SCC)
	<b>Stacked codes</b>	EAN/JAN Composites; GS1 DataBar Composites; GS1 DataBar Expanded Stacked; GS1 DataBar Stacked; GS1 DataBar Stacked Omnidirect.
<b>Depth of field (Typical)</b>	<b>Code 39: 5 mils</b>	6.5 to 21.0 cm
	<b>Code 39: 20 mils</b>	Up to 50.0 cm
	<b>Data Matrix: 15 mils</b>	4.0 to 25.0 cm
	<b>EAN: 13 mils</b>	5.5 to 39.0 cm
<b>Mechanical</b>	<b>Dimensions (LxWxH)</b>	80x52.5x41.37 mm
	<b>Weight</b>	88.8g
	<b>Adjustability</b>	from 0° to 20°
	<b>Color</b>	HP Black
<b>Interface/ Connection</b>	<b>Interface</b>	USB 2.0
	<b>Connection</b>	Type A
<b>Power</b>	<b>Voltage (typical)</b>	5.0V +/- 5% supplied by USB
	<b>Current consumption (typical)</b>	150mA

### Retail Integrated Peripherals

**Drivers****Operating Systems****Compatibility**

Windows Native, OPOS, JPOS

Windows 10 IoT Enterprise for Retail 64-bit\*,\*\*\*

Windows 10 Professional 64-bit\*\*,\*\*\*

Windows Embedded 8.1 Industry Pro Retail 64-bit\*\*

Windows 8.1 Professional 64-bit\*\*

Windows 7 Professional 64-bit\*\*

Windows 7 Professional 32-bit\*\*

Windows Embedded POSReady 7 64-bit\*\*

Windows Embedded POSReady 7 32-bit\*\*

\* Not all features are available in all editions or versions of Windows. Systems may require upgraded and/or separately purchased hardware, drivers, software or BIOS update to take full advantage of Windows functionality. Windows 10 is automatically updated, which is always enabled. ISP fees may apply and additional requirements may apply over time for updates. See <http://www.microsoft.com>

\*\* Not all features are available in all editions of Windows. This system may require upgraded and/or separately purchased hardware to take full advantage of Windows functionality. See <http://www.microsoft.com>.

\*\*\* Full support on all x86-based Windows, NO current support drivers for ARM processor platforms.

---



### Retail Integrated Peripherals

#### HP RP9 Integrated Fingerprint Reader



<b>Model</b>	<b>HP RP9 Integrated Fingerprint Reader</b>	N3R64AA / M7E36AV (Right)/ M7E31AV (Left)
<b>General</b>	<b>Scan Data</b>	8-bit grayscale (256 levels of gray)
	<b>Pixel resolution</b>	508 DPI
	<b>Scan capture area</b>	18mm x 12.80mm
<b>Mechanical</b>	<b>Dimensions (LxWxH)</b>	59x63.23x37.43 (mm)
	<b>Weight</b>	44.8g
	<b>Color</b>	HP Black
<b>Interface/Connection</b>	<b>Interface</b>	USB 2.0
<b>Power</b>	<b>Supply Voltage</b>	5.0V ±5% supplied by USB
	<b>Supply Current Imaging mode</b>	80 mA @ 3.3V
	<b>Supply Current Sleep mode</b>	1350 uA @ 3.3V
<b>Environmental</b>	<b>Temperature</b>	- 20 C to + 70 C
	<b>Humidity</b>	5% to 93% RH w/o condensation
<b>Drivers</b>		Windows Native
<b>Operating Systems</b>	<b>Compatibility</b>	Windows 10 IoT Enterprise for Retail 64-bit*,*** Windows 10 Professional 64-bit*,*** Windows 8.1 Professional 64-bit** Windows Industry 8.1 Pro Retail 64-bit** Windows 7 Professional 64-bit** Windows 7 Professional 32-bit** Windows Embedded POSReady 7 64-bit** Windows Embedded POSReady 7 32-bit** Ubuntu 12.04/13.04/14.04

\* Not all features are available in all editions or versions of Windows. Systems may require upgraded and/or separately purchased hardware, drivers, software or BIOS update to take full advantage of Windows functionality. Windows 10 is automatically updated, which is always enabled. ISP fees may apply and additional requirements may apply over time for updates. See <http://www.microsoft.com>

\*\* Not all features are available in all editions of Windows. This system may require upgraded and/or separately purchased hardware to take full advantage of Windows functionality. See <http://www.microsoft.com>.

### Retail Integrated Peripherals

\*\*\* Full support on all x86-based Windows, NO current support drivers for ARM processor platforms.

### HP RP9 Integrated 2x20 Display (Complex and Non-Complex)



<b>Models:</b>	HP RP9 Integrated 2x20 Display Btm w/Arm	N3R58AA /M7E25AV
	HP RP9 Integrated 2x20 Display Top w/Arm	P5A55AA /M7E26AV
<b>Display type</b>	LCD, LED Backlit	
<b>Brightness</b>	250 nit	
<b>Character Number</b>	2x20	
<b>Viewing Angle</b>	45°	
<b>Dimensions</b>	<b>mm</b>	150.0 (L) * 34.9(w) * 6.4(H)
	<b>Inches</b>	5.5
<b>Temperature Range</b>	<b>Operating:</b>	32° to 104° F (0 to 40° C) at 20% to 85% humidity (non-condensing at ambient)
	<b>Non-operating:</b>	32° to 122° F (0° to 50° C) at 5% to 90% humidity (non- condensing at ambient)
<b>Adjustability</b>	Horizontal Rotation Max 355°	
<b>Weight</b>	top mount arm at 379g, long arm at 476g	
<b>Interface</b>	USB	
<b>Power</b>	<b>Operating voltage</b>	+5VDC
	<b>Idle current</b>	230mA
	<b>Full Load Current</b>	300mA
<b>Drivers</b>	Windows Native	
<b>Compatibility</b>	<b>Product</b>	HP RP9 G1 Retail System
<b>Operating systems</b>	Windows 10 IoT Enterprise for Retail 64-bit*.***	
	Windows 10 Professional 64-bit*,***	
	Windows Embedded 8.1 Industry Pro Retail 64-bit**	

### Retail Integrated Peripherals

Windows 8.1 Professional 64-bit\*\*

Windows 7 Professional 64-bit\*\*

Windows 7 Professional 32-bit\*\*

Windows Embedded POSReady 7 64-bit\*\*

Windows Embedded POSReady 7 32-bit\*\*

\* Not all features are available in all editions or versions of Windows. Systems may require upgraded and/or separately purchased hardware, drivers, software or BIOS update to take full advantage of Windows functionality. Windows 10 is automatically updated, which is always enabled. ISP fees may apply and additional requirements may apply over time for updates. See <http://www.microsoft.com>

\*\* Not all features are available in all editions of Windows. This system may require upgraded and/or separately purchased hardware to take full advantage of Windows functionality. See <http://www.microsoft.com>.

\*\*\* Full support on all x86-based Windows, NO current support drivers for ARM processor platforms.

---

### Retail Integrated Peripherals

#### HP RP9 Integrated Single-Head MSR



<b>Models</b>	<b>HP RP9 Integrated Single-Head MSR</b>	N3R63AA / M7E33AV (Left) M7E34AV (Right)
<b>General</b>	<b>Magnetic stripe formats</b>	ISO 7811, AAMVA
	<b>Card thickness</b>	0.015 to 0.045 in (0.38 to 1.14 mm)
	<b>Indicators</b>	Bi-Colored LED, beeper
<b>Mechanical</b>	<b>Dimensions (LxWxH)</b>	129x70.74x36.52 (mm)
	<b>Weight</b>	112.0g
	<b>Slot width</b>	0.045 in (1.14 mm)
	<b>Color</b>	HP Black
<b>Interface/Connection</b>	<b>Interface</b>	USB 2.0
	<b>Connection</b>	Type A
<b>Power</b>	<b>Voltage (typical)</b>	5 VDC +/- 10%, 50mV ripple max
	<b>Current consumption (typical)</b>	40mA max
<b>Drivers</b>		Windows native, OPOS, JPOS
<b>Operating Systems</b>	<b>Compatibility</b>	Windows 10 IoT Enterprise for Retail 64-bit*,*** Windows 10 Professional 64-bit*,*** Windows Industry 8.1 Pro Retail 64-bit** Windows 8.1 Professional 64-bit** Windows 7 Professional 64-bit** Windows 7 Professional 32-bit** Windows Embedded POSReady 7 64-bit** Windows Embedded POSReady 7 32-bit**

\* Not all features are available in all editions or versions of Windows. Systems may require upgraded and/or separately purchased hardware, drivers, software or BIOS update to take full advantage of Windows functionality. Windows 10 is automatically updated, which is always enabled. ISP fees may apply and additional requirements may apply over time for updates. See <http://www.microsoft.com>

\*\* Not all features are available in all editions of Windows. This system may require upgraded and/or separately purchased hardware to take full advantage of Windows functionality. See <http://www.microsoft.com>.

### Retail Integrated Peripherals

\*\*\* Full support on all x86-based Windows, NO current support drivers for ARM processor platforms.

### HP RP9 Integrated Webcam



<b>Models:</b>	HP RP9 Integrated Webcam	POQ86AA / M7E35AV
<b>General</b>	<b>CMOS Sensor</b>	2M
	<b>Resolution</b>	1920 X 1080
	<b>Image Control</b>	AE, AWB, AGC, Brightness, Contrast, Hue, Saturation, Sharpness, Backlight Comp, Power-Line Frequency, Gamma, White balance and Gain
<b>Field of View</b>	77.5°	
<b>Focus Distance</b>	50cm	
<b>Focus Range</b>	31cm-135cm	
<b>Microphone</b>	X 2	
<b>Mechanical</b>	<b>Dimensions (LxWxH)</b>	125x48.76x39.6 (mm)
	<b>Weight</b>	53.2g
	<b>Color</b>	HP Black
<b>Interface/Connection</b>	<b>Interface</b>	USB 2.0
<b>Power</b>	<b>Voltage (typical)</b>	693 mW
	<b>Current consumption (typical)</b>	200 mA
<b>Drivers</b>		Windows Native
<b>Operating Systems</b>	<b>Compatibility</b>	Windows 10 IoT Enterprise for Retail 64-bit*, *** Windows 10 Professional 64-bit*, *** Windows 8.1 Professional 64-bit** Windows Industry 8.1 Pro Retail 64-bit** Windows 7 Professional 64-bit** Windows 7 Professional 32-bit** Windows Embedded POSReady 7 64-bit** Windows Embedded POSReady 7 32-bit**

\* Not all features are available in all editions or versions of Windows. Systems may require upgraded and/or separately purchased hardware, drivers, software or BIOS update to take full advantage of Windows functionality. Windows 10 is automatically updated,

### Retail Integrated Peripherals

which is always enabled. ISP fees may apply and additional requirements may apply over time for updates. See <http://www.microsoft.com>

\*\* Not all features are available in all editions of Windows. This system may require upgraded and/or separately purchased hardware to take full advantage of Windows functionality. See <http://www.microsoft.com>.

\*\*\* Full support on all x86-based Windows, NO current support drivers for ARM processor platforms.

---

### Summary of Changes

Date of change:	Version History:		Description of change:
		From v1 to v2	

Copyright © 2016 HP Development Company, L.P

All rights reserved. Microsoft, Windows, Windows 7, Windows 8, and Windows 10 are registered trademarks or trademarks of Microsoft Corporation in the U.S. and/or other countries. Intel®, Celeron®, Pentium® and Core™ are registered trademarks or trademarks of Intel Corporation in the U.S. and/or other countries. Linux is the registered trademark of Linus Torvalds in the U.S. and other countries. Bluetooth® is a registered trademark of its proprietor and used by HP Inc. under license. ENERGY STAR is a registered trademark owned by the U.S. Environmental Protection Agency.

The information contained herein is subject to change without notice. The only warranties for HP products are set forth in the express limited warranty statements accompanying such products. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.